



BATTERY-BOX HVS+



KEY FEATURES



Ultra Safety

LFP expertise since 2002
1M+ systems in 100+ countries
Safety design from cell to pack




Intelligent Management

Automatic SOC adjustment
Remote diagnosis and OTA



High Performance

High efficiency
Max. 12.8kW charge/discharge
power per tower



Flexibility

Modular design
Built-in balancing optimizer
Extend anytime at any SOC



Easy Installation

Patented internal plug connection
One-click configuration



Perfect Compatibility

Compatible with leading single
& three phase inverters

BATTERY-BOX HVS+



HVS+ 5.1



HVS+ 12.8



3 x HVS+ 12.8

Maximum capacity of

38.4 kWh

TECHNICAL PARAMETERS HVS+



HVS+ 5.1



HVS+ 7.7



HVS+ 10.2



HVS+ 12.8

PERFORMANCE

Battery Module	HVS+ (2.56 kWh, 102.4 V, 38.5 kg)			
Number of Modules	2	3	4	5
Usable Energy ^[1]	5.12 kWh	7.68 kWh	10.24 kWh	12.8 kWh
Max. Output Current ^[2]	25 A	25 A	25 A	25 A
Peak Output Current ^[2]	55 A, 15 s	55 A, 15 s	55 A, 15 s	55 A, 15 s
Nominal Voltage	204.8 V	307.2 V	409.6 V	512 V
Operating Voltage	160 - 230.4 V	240 - 345.6 V	320 - 460.8 V	400 - 576 V
Dimensions(H/W/D)	747 x 610 x 282 mm	987 x 610 x 282 mm	1227 x 610 x 282 mm	1467 x 610 x 282 mm
Weight	91.6 kg	130.1 kg	168.6 kg	207.1 kg

GENERAL DATA

Operating Temperature	-10°C to +50°C
Cell Technology	Lithium Iron Phosphate (LiFePO ₄)
Communication	CAN / RS485
IP Class	IP55
Round-trip Efficiency	≥ 95%
Installation Scene	Indoor / Outdoor Installation
Installation Mode	Floor Stand
Storage Humidity	5%~95%
Altitude	< 3000 m
Certification	VDE2510-50 / IEC62619 / CE / UKCA / UN38.3
Applications	ON Grid / ON Grid + Backup / OFF Grid
Warranty ^[3]	10 Years

[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at + 25°C. System Usable Energy may vary with different inverter brands.

[2] Power derating will occur between -10°C and +5°C.

[3] Conditions apply. Refer to BYD Battery-Box HVS+ Limited Warranty Letter.